

TECHNICAL DATA SHEET - TECHSPAN 1502CS EXTRUDER WELDER

- High quality heavy duty Extruder Welder
- Compact with integrated air supply
- Accepts 3mm or 4mm plastic welding rod
- Separate control of preheat & melt
- Tempered steel screw & barrel
- No wearing parts on rod feed system
- 0.6kg/hr with 3mm rod
- 1.7kg/hr with 4mm rod
- For welding : PE, PP
- 2 year warranty *



Advanced compact & very robust design with decisively less wear points than other extruders. Patented temperature measurement. Built-in stand. Full range of welding shoes available. Adjustable handle positions. Optional rod de-reeler and full range of welding rods available.

Technical Data

| | | |
|----------------------------|--------|--------|
| Voltage | V | 230 |
| Frequency | Hz | 50/60 |
| Welding Capacity, max | kg/hr | 1.7 |
| Power Consumption, drive | kW | 0.8 |
| Power Consumption, melt | kW | - |
| Power Consumption, preheat | kW | 3.4 |
| Airflow | l/min. | 300 |
| Welding Rod | mm | 3 or 4 |
| Weight | kg | 5.2 |

* Warranty does not cover heating elements or normal wearing parts.

* Motors are covered for 1 year.

Australia:

P O Box 1012, Mascot, NSW 1460, Sydney
 Ph: 1-800 148 791 Fax: 1-800 148 799
sales@techspanonline.com www.techspanonline.com

New Zealand:

P O Box 15262, New Lynn, Auckland
 Ph: ++64 9 8276567 Fax: ++64 9 827 6596
sales@techspanonline.com www.techspanonline.com

TECHSPAN GROUP
 PLASTIC WELDING SYSTEMS

www.techspanonline.com