

TECHNICAL DATA SHEET - TECHSPAN 3002CS-5 EXTRUDER WELDER

- High quality heavy duty Extruder Welder
- Integrated air supply
- Accepts 4mm or 5mm plastic welding rod
- Separate control of preheat & melt
- Tempered steel screw & barrel
- No wearing parts on rod feed system
- 1.8kg/hr with 4mm rod
- 3.7kg/hr with 5mm rod
- For welding : PE, PP, PVC, PVDF
- 2 Year warranty *



Advanced compact & very robust design with decisively less wear points than other extruders. Cold start prevention. Patented temperature measurement. Built-in stand. Full range of welding shoes available. Adjustable handle positions. Optional rod de-reeler and full range of welding rods available.

Technical Data

Voltage	V	230
Frequency	Hz	50/60
Welding Capacity, max	kg/hr	3.7
Power Consumption, drive	kW	0.8
Power Consumption, melt	kW	0.6
Power Consumption, preheat	kW	2.3
Airflow	l/min.	300
Welding Rod	mm	4 or 5
Dimensions	mm	
Weight	kg	7.8

* Warranty does not cover heating elements or normal wearing parts.

* Motors are covered for 1 year.

Australia:

P O Box 1012, Mascot, NSW 1460, Sydney
 Ph: 1-800 148 791 Fax: 1-800 148 799
 sales@techspanonline.com www.techspanonline.com

New Zealand:

P O Box 15262, New Lynn, Auckland
 Ph: ++64 9 8276567 Fax: ++64 9 827 6596
 sales@techspanonline.com www.techspanonline.com

TECHSPAN GROUP
 PLASTIC WELDING SYSTEMS

www.techspanonline.com